





<b>Model O431 I2</b>				
<b>Dimensions</b>	<b>Machine</b>		<b>with crate</b>	
width	19-1/8" (48,6 cm)		27" (68,6 cm)	
height	66-7/8" (169,9 cm)		78" (198,1 cm)	
depth	37-5/8" (95,6 cm)		48" (121,9 cm)	
<b>Weight</b>	500 lbs (226,7 kg)		650 lbs (294,8 kg)	
<b>Electrical*</b>	<b>1 Phase, 208-240 VAC, 60Hz</b>		<b>3 Phase, 208-240 VAC, 60Hz</b>	
running amps	Air Cooled 23A	Water Cooled 22A	Air Cooled 19A	Water Cooled 18A
connection type	NEMA L6-30P	NEMA L6-30P	NEMA L15-30P	NEMA L15-30P
International Option	1 Phase, 220-240 VAC, 50Hz or 3 Phase, 380-415 VAC, 50Hz			
<b>Compressor</b>	15,000 Btu/hr Cabinet - 1,300 Btu/hr Compressor (R-134a)			
<b>Drive Motor</b>	Two - 2 hp			
<b>Air Flow</b>	Air cooled units require 3" (7,6 cm) air space on both sides and back and open at the top.			
<b>Plumbing Fittings</b>	Water cooled units require 1/2" N.P.T. water and drain fittings. Maximum water pressure of 130 psi. Minimum water flow rate of 3 GPM per barrel. Ideal EWT of 50°-70°F.			
<b>Hopper Volume</b>	Two - 5.5 gallons (20,82 liters)			
<b>Freezing Cylinder Volume</b>	Two - 1 gallon (3,79 liters)			

Continuous research leads to ongoing product improvements; therefore, these specifications are subject to change without notice and should not be used as installation specifications. \*Machine requires a dedicated electrical circuit.

Distributed by:



A VOLLRATH® COMPANY

Representative in CIS Alfa Pack

Ukraine, Kiev, Obolonskaya naberezhnaya 7/3, office 1

tel.: +38(044) 587-56-17 (-18, -19)

fax: +38(044) 581-78-20

http://www.alfapack.com.ua

e-mail: alfapack@alfapack.com.ua

Certified, Listed  
and/or Recognized by:



ISO 9001:2008 Registered | STMF-104D 3/13